



## Partition Doors

### Room Dividers

Product code **BFR CON**

A top hung vinyl concertina partition with an internal steel pantograph frame. All systems made to measure to suit actual site dimensions and can be supplied either single wing, bi-parting or with floating units. Option for floor supported in the absence of a suitable support fixing.

### Specifications:- Room Dividers

#### Construction:

The partition consists of an internal framework of electro-galvanised 6mm steel rods and nylon hinges at 1 metre centres..

#### Operation:

Manual.

#### Finish:

Fabric backed vinyl, available in 24 colours with a 5-year manufacturer's warranty. It is fully washable and has been treated with a water based acrylic solution, giving an extra stain, mould, mildew, fungi and bacteria resistant finish.

#### Fire Rating:

Class '0' & class '1' to BS476 is standard with the option for The Furniture and Furnishings (Fire) (Safety) Regulations 1988, Schedule 1, Part 1, when using ignition source 5 of BS 5852:1982 Part 2.

#### Maximum Height:

6000mm

#### Maximum Width:

Unlimited

#### Head Track:

SAA track - 33mm x 34mm

### Acoustic Rating:

15dB - 8 kgs per square metre

24dB - 11 kgs per square metre

32dB - 16 kgs per square metre

35db - 21 kgs per square metre

### Stack Dimensions:

Thickness of stack ~ 255mm

Narrow Stack Depth of 15dB = 1 / 6 width of leaf + 125mm

Depth of 24dB = 1 / 5 width of leaf + 125mm

Depth of 32dB = 1 / 4 width of leaf + 125mm

Depth of 35dB = 1 / 4 width of leaf + 125mm

Wide Stack Thickness of stack ~ 410mm

Depth of 15dB = 1 / 6 width of leaf + 125mm / 2

Depth of 24dB = 1 / 5 width of leaf + 125mm / 2

Depth of 32dB = 1 / 4 width of leaf + 125mm / 2

### Stacking:

Single wing / bi-parting/floating unit

### Edge Profiles:

SAA

### Locking:

Magnetic latches are supplied as standard on all systems with option for a lock.