



## Security Shutter Doors

Product code **BFR CON/38/44 - Built on**

Generally constructed of a double walled extended aluminium 38mm deep lath interlocked together & retained by nylon end locks. All shutters complete with canopies & come in polyester powder coating finish white as standard options include Push up/Rod crank, Tape and electric operation.

### Specifications:- Security Shutters - Built on

#### **Curtain:**

Constructed from 38mm continental style, double skin extruded aluminium non-vented lath with lateral movement contained by nylon end locks with a bottom rail to suit.

#### **Shutter Housing:**

Constructed from roll formed aluminium in two sections, top and bottom box removable for installation and maintenance purposes.

#### **Electrical Operation:**

Single phase powered by SOMFY tubular motors, 240volts with .05 -2.5 amps of draw dependent upon shutter size.

#### **Finish Options:**

Apart from our standard colours, this product can be powder coated to any B.S or R.A.L. colours you may require.

#### **Barrel:**

Constructed from 60mm octagonal tube with roller bearings on non-drive end and operator on opposite.

#### **End Plates:**

Die - cast aluminium to suit shutter housing.

#### **Electrical Optional Extras:**

Key switch, remote control, group commands.

#### **Optional Extras:**

High security guide channels, emergency over ride systems and sill angles.

#### **Installation:**

If required installation can be carried out by our own fully experienced fitting teams.

#### **Side Guides:**

Constructed from extruded aluminium with an internal box section for strength and installation complete with nylon brush seals for smooth operation.

#### **Operation:**

Operation is dependent of shutter size by one of the following ,swivel belt winder, geared belt winder, rod crank or spring loaded.

**Colours:**

Curtains - white, beige, brown  
 Guides & boxes - white, brown

